

BENDING MACHINE FOR IRON

DESCRIPTION

The **STOUT BENDING MACHINES** for concrete reinforcing steel rods are the result of years of experience. The machines are the result of the latest building technologies applied to the experience achieved over the years. Machines that are standardly produced with a wide turning plate, that permits to obtain larger curving radii and with long saddles, that allow to perform the "double bending".

Formidable machines, with high-performance and easy to maintain, on which the manufacturer believes strongly and grants 2 year warranty on all mechanical components.

Scan to
access the
website



TECHNICAL DATA

MODEL	RPM	POWER (HP/Kw)	65 KG/ MM2 Ø 1	65 KG/ MM2 Ø 2	65 KG/ MM2 Ø 3	85 KG/ MM2 Ø 1	85 KG/ MM2 Ø 2	85 KG/ MM2 Ø 3	SIZE	WEIGHT	OIL
									(cm)	(Kg)	(Kg)
P34	11	3/2.2	30 mm 1,18 in	22 mm 0,87 in	18 mm 0,71 in	28 mm 1,10 in	20 mm 0,79 in	16 mm 0,63 in	75x80x85	285	5
P38	9	4/3	34 mm 1,34 in	26 mm 1,02 in	20 mm 0,79 in	32 mm 1,26 in	24 mm 0,94 in	18 mm 0,71 in	86x90x85	365	8
P44	6	4/3	38 mm 1,50 in	30 mm 1,18 in	24 mm 0,94 in	36 mm 1,42 in	28 mm 1,10 in	22 mm 0,87 in	105x95x89	500	13
P54	6	5,5/4	44 mm 1,73 in	34 mm 1,34 in	28 mm 1,10 in	40 mm 1,57 in	32 mm 1,26 in	24 mm 0,94 in	105x95x89	585	13
P56	5	7,5/5,5	46 mm 1,81 in	36 mm 1,42 in	30 mm 1,18 in	42 mm 1,65 in	34 mm 1,34 in	26 mm 1,02 in	130x95x89	710	13