

MANTA SPECIAL

Job-Site Industry

BRIDGE SAW MACHINE

CHARACTERISTICS

MANTA ED 120-150-200 SPECIAL is a rugged and inexpensive machine guaranteeing an extremely accurate cutting. Head sliding on two chromium-plated and ground bars by means of linear ball-bearings. It is equipped with a submersible pump placed inside the base to collect the water cooling the blade. Vertical head motion by means of a handwheel for a fast and stable adjustment. Tilting head for 45° cuts. Integrated angle legs.

<u>ACCESSORIES</u>: Adjustable stop, set of servicing wrenches, holes for machine hoisting.

<u>OPTIONALS</u>: Diamond cutting blade, side stop, diagonal square, side table, battery laser pointer.

Scan to access the website





FEATURES

ARTICLE	MODEL	DIAMETER	RPM	POWER	SLAB LENGHT	SLAB THICKNESS
		(mm)		(Kw - Volt)	(mm)	(mm)
120311	MANTA 120 SP	350 - 30	2800	2,2 - 230	1200	110
120305	MANTA 120 SP	450 - 30	2800	4 - 400	1200	150
120356	MANTA 150 SP	350 - 25.4	2800	2,2 - 230	1500	150
120400ED	MANTA 150 SP	450 - 30	2800	4 - 400	1500	150
120457	MANTA 200 SP	450 - 30	1400	2,2 - 230	2000	150
120451	MANTA 200 SP	450 - 30	1400	4 - 400	2000	150

^{*} Voltage and power upon request on each model. All models mount chromed 50mm diameters bars.

SPARE PARTS

Immersion pump



Side roller table



